

PIXMA G2560

HIGH YIELD, ECONOMICAL PRINTING AT DEADLINE- BEATING SPEEDS

Entry level, refillable ink tank multifunctional printer featuring fast print speeds and usability improvements – ideal for home, student or office use.



- **Endless low-cost printing**
Keep on printing while keeping costs down thanks to huge yields of up to 12,000 pages (26% more in Economy mode³) from 2 black ink bottles, or 7,700 pages with a single set of colour bottles¹
- **High speed, high quality**
Depend on quality at high speed (10.8 ipm in black / 6 ipm in colour²), with pigment black ink ensuring pin-sharp text and dye colour inks delivering vivid colour photos
- **Easy maintenance**
Minimise downtime and meet every deadline with ease, with a user-replaceable maintenance cartridge that ensures dependable, day after day performance
- **Thoughtful design**
Refill ink tanks without fuss or effort using handy non-squeeze bottles with unique key type nozzles that ensure each ink bottle can only refill its equivalent tank
- **Get creative**
Experiment with diverse media types and sizes including magnetic photo paper, restickable photo paper, or even print your own banners up to 1.2 metres in length



Fast Printing



Borderless Photo Printing



Integrated Ink Tanks



Replaceable ink maintenance cartridge



1,200mm
Banner Printing



Hybrid Ink System

PRODUCT RANGE



PIXMA G3520



PIXMA G2560



PIXMA G3560

PIXMA G1520

PIXMA G2520

PIXMA G3520

PIXMA G2560

PIXMA G3560

PIXMA G4511

Live for the story_

¹ Page yield of ink bottle used for initial setup is lower than a replacement as a certain amount of ink is used to fill the print head during setup. Page yield is the estimated value based on Canon's individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup. Black and colour page yields are not to be combined. Page yield varies significantly depending on contents printed and other factors.

TECHNICAL SPECIFICATIONS

PIXMA G2560

GENERAL SPECIFICATIONS		Copy Functions	Document Copying, Photo Copying, Borderless copy, 2-on-1 and 4-on-1 copy, Frame erase copy, ID copy
Functions	High Speed Print, Scan & Copy	Copy Zoom	25 - 400% (in 1% increments) Fit to page A5 to A4, B5 to A4, A4 to A5 and A4 to B5
PRINTER SPECIFICATIONS		GENERAL	
Print Resolution	Up to 4800 x 1200 dpi ^[1]	Display	Full Dot LCD
Print Technology	2 FINE Print Head (Black and Colour) Refillable ink tank printer approx. 10.8 ipm ^[2] approx. 6.0 ipm ^[2]	Display Languages	32 Languages Selectable: Japanese, English(mm & inch), German, French, Italian, Spanish, Dutch, Portuguese, Norwegian, Swedish, Danish, Finnish, Russian, Czech, Hungarian, Polish, Slovene, Turkish, Greek, Simplified Chinese, Traditional Chinese, Korean, Indonesian, Slovakian, Estonian, Latvian, Lithuanian, Ukrainian, Romanian, Bulgarian, Croatian, Vietnamese
Mono Print Speed	Borderless 10x15cm : Approx. 45 seconds ^[3]		Hi-Speed USB (USB B Port)
Colour Print Speed	Yes		Easy-PhotoPrint Editor Software ^[11]
Photo Print Speed	A4, LTR, 4" x 6", 5" x 7", 7" x 10", 8" x 10", Square (89 mm x 89 mm), Square(127 mm x 127 mm), Card Size(91 mm x 55 mm) ^[4]	Standard Interface	Windows 10, Windows 8.1, Windows 7 SP1 Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.
Borderless Printing	Manual operation	Printer Features	Printer driver, IJ Printer Assistant Tool and IJ Network Device Setup Utility are available with following OS.
Two Sided Printing		OS Compatibility	Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
CARTRIDGES AND YIELDS			Chrome OS
Standard Ink Cartridges	GI-51 <PGBK> GI-51 <C> GI-51 <M> GI-51 <Y>	Minimum System Requirements	Mac: OS X 10.12.6 ~ macOS 10.15 ^[12] Windows: 2.0GB or more Mac: 1.0GB or more Note: for bundled software installation. The necessary amount of hard disk space required. Display: 1024 x 768 XGA Printer Driver IJ Printer Assistant Tool Easy-PhotoPrint Editor (download)
Cartridge Yield (Plain paper)	A4 colour documents printing ^[5] Black: 6,000 pages (Economy mode 7,600 pages) ^[6] Colour: 7,700 pages * Estimated supplemental yield		
Cartridge Yield (Photo print)	10x15cm colour photo printing ^[7] Colour: 2,200 photos * Estimated supplemental yield	Software Included	
PAPER SUPPORT		PHYSICAL FEATURES	
Paper Types	Plain Paper Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-201) Matte Photo Paper (MP-101), Glossy Photo Paper "Everyday Use" (GP-501) High Resolution Paper (HR-101N), Envelope, Photo Paper Plus Semi-gloss (SG-201), Cardstock Restickable Photo Paper(RP-101) Magnetic Photo Paper(MG-101) Dark Fabric Iron on Transfers (DF-101), Light Fabric Iron on Transfers (LF-101), Double sided Matte Paper (MP-101D) Rear Tray: Max. 100 sheets (plain paper)	Weight	approx. 6.4 kg
Maximum Paper Input		Dimensions (W x D x H)	Approx. 445 x 330 x 167
Paper Sizes	A4, A5, A6, B5, LTR, LGL, Executive (184.2 mm x 266.7 mm), Legal (215 mm x 345 mm), 4" x 6", 5" x 7", 7" x 10", 8" x 10", Envelopes DL, Envelopes COM10, Envelopes C5, Square (89 mm x 89 mm), Square (127 mm x 127 mm), Card Size(91 mm x 55 mm) [Custom size] width 55 mm - 216 mm, length 89 mm - 1200 mm	Acoustic Noise Levels	approx. 51.0dB(A) ^[13]
Paper Weight	Rear Tray: Plain paper: 64 - 105 g/m ² Canon specialty paper: max paper weight : approx. 275 g/m ² (Photo Paper Plus Glossy II PP-201)	Operating Temperature	5-35°C
SCANNER SPECIFICATIONS		Operating Humidity	10-90%RH (no dew condensation)
Scanner Type	CIS flatbed photo and document scanner	Power Source	AC 100-240V, 50/60Hz
Scanner Resolution (Optical)	600 x 1200 dpi ^[8]	Power Consumption	Off: Approx. 0.2W Standby (USB connection to PC): Approx. 0.6W Standby (all ports connected): Approx. 0.6W Time to enter Standby mode: 11 minutes 4sec Copying: Approx. 15W ^[14] 0.1 kWh ^[15]
Line Scanning Speed	Colour: 3.5 ms/line(300dpi) Greyscale: 1.5 ms/line(300dpi) ^[9]	Typical Electricity Consumption	
Scanning Depth (Input / Output)	Colour: RGB each 16bit / 8bit Greyscale: 16 bit / 8 bit	Footnote:	
Maximum Document Size	A4/LTR	^[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch	
COPIER SPECIFICATIONS		^[2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.	
Copy Speed	sFCOT: Approx. 23 sec ^[10] sESAT: Approx. 3.2 ipm ^[10]	^[3] Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.	
Multiple Copy	99 copies (max.)	^[4] Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers	
		^[5] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart and continuous printing simulation with the replacement after initial setup.	
		^[6] The economy mode reduces the black ink consumption by lowering the density, 26% more pages than the standard mode can be printed	
		^[7] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement after initial setup.	
		^[8] Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.	
		^[9] The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.	



Live for the story_

² Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

³ The economy mode reduces the black ink consumption by lowering the density, 26% more pages than the standard mode can be printed

TECHNICAL SPECIFICATIONS

PIXMA G2560

Footnote:

[10] Colour document copy speed is measured based on average of sFCOT and sESAT in Performance Test of ISO/IEC 29183 standard. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

[11] The Easy-PhotoPrint Editor software requires an Internet connection and is compatible with the following operating systems; Microsoft Windows 10 (64-bit/32-bit), Microsoft Windows 8.1 (64-bit/32-bit), Microsoft Windows 7 SP1 (64-bit/32-bit), macOS High Sierra v10.13, macOS Sierra v10.12, Mac OS X El Capitan v10.11 and Mac OS X El Capitan v10.10.5. Minimum Windows and macOS/Mac OS X requirements are: 2GB of RAM and a monitor with 1024x768 resolution.

[12] Some functions may not be available with these Operating Systems. Please refer to the manual or website for details.

[13] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.

[14] Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

[15] Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Standard disclaimers

- All specifications subject to change without notice.
- Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield
- All brand and product names are trademarks of their respective companies.
- Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2020

HIGH YIELD, ECONOMICAL PRINTING AT DEADLINE-BEATING SPEEDS

PIXMA G2560

Entry level, refillable ink tank multifunctional printer featuring fast print speeds and usability improvements – ideal for home, student or office use.

Sales Start Date: December 2020



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA G2560	4466C008AA	4549292167917	<Please fill in RRP>

CONSUMABLES:

Product Name	Mercury Code	EAN Code
Standard size		
GI-51PGBK	4529C001AA	4549292169546
GI-51C	4546C001AA	4549292169829
GI-51M	4547C001AA	4549292169843
GI-51Y	4548C001AA	4549292169867
Maintenance Cartridge		
MC-G02	4589C001AA	4549292171518

MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)	Net Weight (kg)
PIXMA G2560	Individual	1	520.5	476	255.5	9.45	TBC
	Pallet (Upper)	16	1051	984	1032.5	152.87	TBC
	Pallet (Bottom)	20	1051	984	1289.5	190.66	TBC

What's in the box?

- PIXMA G2560
- 5 high yield ink bottles (2x Black and 1x C/M/Y)
- Print Heads
- Power cord
- Setup CD-ROM
- Manuals and other documents

Canon

Live for the story_