DYMO

Rhino[™] 4200



Compact, Time-Saving Label Maker for On-The-Go Pros

- · Familiar computer-style keyboard with country-specific layout for fast and easy text entry
- One-Touch "Hot Keys" provide shortcuts for creating and formatting wire/cable wraps, flags, Code 39 and Code 128 bar codes, fixed-length, general and breaker labels
- "Favorites" key provides single-key access to your most commonly used labels, symbols and terms
- Avoid repeated steps with the "Custom" key customize and save settings for individual label formats
- Pre-programmed library with 150 symbols and terms for security, electrical, pro A/V, and facilities management
- Integrated rubber bumpers help prevent damage from accidental drops and falls
- · Large back-lit display is easy to read, even in dimly-lit work areas
- Prints 57% faster than the competition*
- *Based on independent testing of Rhino 4200 vs. Brother PT-1400 and Brother PT-7100 in default settings



TAPES

Single Unit Includes:

- Rhino 4200 Label Maker
- 12 mm White Vinyl Label Cartridge
- Quick Reference Guide

Kit includes everything in single unit plus:

- Carry Case
- Rechargeable Battery
- AC Charging Adaptor





| Quick Specs | |
|---------------------------------|-------------------------------------|
| Unit Dimensions (H x W x L) | 215 x 103 x 57 mm |
| Weight (excluding battery) | 540 g |
| Mac [®] /PC Compatible | No |
| Accepts Label Sizes | 6mm, 9mm, 12mm, 19mm |
| Tape Platform | IND Rhino™ |
| Resolution | 180 dpi |
| Printing System | Thermal Transfer |
| Print Speed | 15mm/sec |
| Barcodes | Yes, Code 39 & Code 128 |
| Cutter Type | Manual |
| Batteries | 6 AA or Rechargeable (not included) |
| AC Adapter | Yes (not included) |
| Networking | No |
| Country of Origin | China |

| ltem Number | Description | | Length (cm) | Width (cm) | Height (cm) | Weight (kg) | QTY | EAN | Customer Price | |
|----------------|-----------------------------|--------|----------------|---------------|----------------|----------------|-----|----------------|-------------------|--|
| S0955950 | RHINO 4200 UK/IRL | Unit | 8.8 | 15.6 | 23.0 | 0.7 | 1 | 3501170955956 | | |
| | | | - | - | - | - | - | - | | |
| | | | 23.0 | 20.0 | 35.0 | 3.2 | 4 | 13501170955953 | | |
| | | Pallet | 120.0 | 80.0 | 120.0 | 216.3 | 240 | - | | |
| Accessories | | | | | | | | | | |
| S0721430 | RHINO AC Adapter | Unit | 11.5 | 5.9 | 8.9 | 0.2 | 1 | 5411313400756 | | |
| S0895840 | Rechargeable battery | Unit | 8.5 | 3.2 | 8.9 | 0.1 | 1 | 3501170895849 | | |
| | | | | | | | | | | |
| S0955950 | KITCASE R4200 QWERTY UK/IRE | Unit | 9.2 | 27.5 | 26.5 | 1.1 | 1 | 3501178529920 | | |
| | | | - | - | - | - | - | - | | |
| | | Case | 29.0 | 28.0 | 29.0 | 3.8 | 3 | 13501170841393 | | |
| | | Pallet | 120.0 | 80.0 | 15.0 | 25.0 | 180 | - | | |

Rhino[®] 4200 | Compatible Labels



IND Vinyl

Ideal for both indoor and outdoor applications. Available in the widest range of colors that meet OSHA, ANSI and ISO color standards.

- UL recognized component to UL 969
- RoHS compliant
- Temperature rating: -40°C to 80°C

IND Flexible Nylon

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- · RoHS compliant
- Temperature rating: -10°C to 80°C

IND Permanent Polyester

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.

- UL recognized component to UL 969
- RoHS compliant
- For flat surfaces only
- Temperature rating: -40°C to 150°C

IND Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables.

- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- UL recognized as a component to UL 224
- · RoHS compliant
- Temperature rating: -55° C to 135°C

| IND Compatible Labels | | | | | | | | | | | | |
|-------------------------|------------|---------|----------|-------|-------|---------|---------|---------|---------|---------|---------|---------|
| Width | Length | А | А | А | А | А | А | А | А | А | А | А |
| IND VINYL | | | | | | | | | | | | |
| 9mm | 5.5m | 18443 | - | - | - | - | - | 1805437 | - | - | - | - |
| 12mm | | 18444 | - | 18432 | 18435 | 1805413 | 1805416 | 1805435 | 1805414 | 1805243 | 1805415 | 1805412 |
| 19mm | | 18445 | - | 18433 | 18436 | 1805419 | 1805422 | 1805436 | 1805420 | 1805417 | 1805421 | 1805418 |
| IND PERMANENT POLYESTER | | | | | | | | | | | | |
| 6mm | | 1805442 | 1805440 | - | - | 1805441 | - | - | - | - | - | - |
| 9mm | 5.5m | 18482 | 18508DM0 | - | - | 18485 | - | - | - | - | - | - |
| 12mm | | 18483 | 622289 | - | - | 18486 | - | - | - | - | - | - |
| 19mm | | 18484 | 622290 | - | - | 18487 | - | - | - | - | - | - |
| IND FLEXIBL | E NYLON. | | | | | | | | | | | |
| 12mm | 3.5m | 18488 | - | 18490 | - | - | - | - | - | - | - | - |
| 19mm | 3.5m | 18489 | - | 18491 | - | - | - | - | - | - | - | - |
| IND HEAT-SI | IRINK TUBE | | | | | | | | | | | |
| 6mm | 1.5m | 18051 | - | 18052 | - | - | - | - | - | - | - | - |
| 9mm | | 18053 | - | 18054 | - | - | - | - | - | - | - | - |
| 12mm | | 18055 | - | 18056 | - | - | - | - | - | - | - | - |
| 19mm | | 18057 | - | 18058 | - | - | - | - | - | - | - | - |

Country of Origin: Belgium

DISTRIBUTED BY:

Newell Europe Sàrl Chemin de Blandonnet 10 1214 Vernier – Switzerland WWW.DYMO.COM



DYMO

INTERNAL USE ONLY. NOT FOR DISTRIBUTION.