

PIXMA G7050

MEGATANK


4-IN-1 WITH

ADF

Print, scan, copy and fax from one sleek model, boosting uptime with a 350-sheet plain paper capacity, auto 2-sided printing and 35-sheet ADF. Print up to 18,000 pages from 3 ink bottles or 7,700 from a colour set¹ for high quality and low costs.



- Sleek multifunctionality**
 4-in-1 functionality, a 2-line mono LCD and 35-sheet ADF for multipage copying and scanning ensure compact practicality, ideal for budding entrepreneurs or a busy small office
- Supercharged productivity**
 Print up to 18,000 pages from 3 black bottles (7,700 from a colour set¹) and keep working with auto 2-sided printing and a 350-sheet capacity via a 2-way feed
- Wireless and local connectivity**
 Link up with Wireless Connect and take control via the Canon PRINT app. Print with AirPrint (iOS), Mopria (Android) and Windows 10 Mobile, or link up via Ethernet
- Stay professional**
 Get professional results with fast print speeds and a pigment black ink for crisp, sharp text. Print vivid borderless photos in sizes of up to A4 with the colour inks
- Manage and control**
 Remotely monitor your printer's ink levels, usage and status with remote management tools for total control



PRODUCT RANGE



PIXMA GM2050
 PIXMA GM4050
 PIXMA G5050
 PIXMA G6050
PIXMA G7050

Canon

Live for the story_

¹ Page yield of ink bottle used for initial setup is lower than a replacement as a certain amount of ink is used to fill the print head during setup. Page yield is the estimated value based on Canon's individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup.

TECHNICAL SPECIFICATIONS

PIXMA G7050

GENERAL SPECIFICATIONS

Functions	Wi-Fi, Ethernet, Print, Copy, Scan, Fax, Cloud Link
PRINTER SPECIFICATIONS	
Print Resolution	Up to 4800 x 1200 dpi ^[1]
Print Technology	2 FINE Cartridges (Black and Colour) Refillable ink tank printer
Mono Print Speed	Approx. 13.0 ipm ^[2]
Colour Print Speed	Approx. 6.8 ipm ^[2]
Photo Print Speed	Borderless 10x15cm : Approx. 45 seconds ^[3]
Borderless Printing	Yes A4, LTR, 4"x6", 5"x7", 7"x10", 8"x10", Square (5"x5", 4"x4", 89x89mm)
Two Sided Printing	Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

CARTRIDGES AND YIELDS

Standard Ink Cartridges	GI-50 <PGBK> GI-50 <C> GI-50 <M> GI-50 <Y>
Cartridge Yield (Plain paper)	A4 colour documents printing ^[4] Black: 6,000 pages Colour: 7,700 pages * Estimated supplemental yield
Cartridge Yield (Photo print)	10x15cm colour photo printing ^[5] Colour: 2,200 photos * Estimated supplemental yield
PAPER SUPPORT	
Paper Types	Plain Paper High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201) Photo Paper Pro Platinum (PT-101) Photo Paper Pro Luster (LU-101) Photo Paper Plus Semi-gloss (SG-201) Glossy Photo Paper "Everyday Use" (GP-501) Matte Photo Paper (MP-101) Envelope Removable Photo Stickers (RP-101) Magnetic Photo Paper (MG-101) Double sided Matte (MP-101D) Dark Fabric Iron-on transfers (DF-101)
Maximum Paper Input	Rear Tray: Max. 20 sheets (photo paper) or Max. 100 sheets (plain paper) Cassette: Max. 250 sheets (plain paper) Up to 35 Sheets (1-sided)
Automatic Document Feeder	
Paper Sizes	Rear Tray: A4, A5, B5, LTR, LGL, 4"x6", 5"x7", 7"x10", 8"x10", Envelopes (DL, COM10), Square (5"x 5", 4"x4", 89x89mm) [Custom size] width 55mm - 215.9 mm, length 89mm - 676mm Cassette: A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm ADF: A4, LTR, LGL
Paper Weight	Rear Tray: Plain paper: 64 - 105 g/m ² Canon photo paper: up to 300 g/m ² (Photo Paper Pro Platinum PT-101) Cassette: Plain paper: 64 - 105 g/m ²

SCANNER SPECIFICATIONS

Scanner Type	Flatbed, ADF and CIS colour scanner
Scanner Resolution (Optical)	1200 x 2400 dpi ^[6]
Line Scanning Speed	Colour: 3.5 ms/line (300dpi) Greyscale: 1.5 ms/line (300dpi) ^[7]
Scanning Depth (Input / Output)	Colour: RGB each 16bit/8bit Greyscale: 16 bit / 8 bit
Maximum Document Size	A4/LTR (216 x 297 mm) ADF: A4, LTR, LGL

COPIER SPECIFICATIONS

Copy Speed	sFCOT/Simplex (colour): Approx. 22 sec ^[8] sESAT/Simplex (colour): Approx. 3.9 ipm ^[8] ESAT/Simplex ADF (colour): Approx. 4.3 ipm ^[8] 99 copies (max.)
Multiple Copy	Document Copying, Photo Copying, Borderless copy, 2-sided copy, 2-on-1 and 4-on-1 copy, Frame erase copy, ID copy
Copy Functions	25 - 400% (in 1% increments) Fit to page A5 to A4, B5 to A4, A4 to A5 and A4 to B5
Copy Zoom	

FAX SPECIFICATIONS

Fax Type	Super G3 / Colour
Fax Resolution	Mono: up to 300 x 300dpi Colour: 200 x 200 dpi
Transmission Speed	Mono: approx. 3 sec. (33.6kbps) ^[12] Colour: approx. 1 min. (33.6kbps) ^[12] Up to 50 pages ^[13]
Fax Memory	Max. 19 locations
Group Dial	

INTERFACE

Display Type & Size	Full Dot LCD
Display Languages	32 Languages Selectable: Japanese/English (mm & inch)/German/French/Italian/Spanish/Dutch/Portuguese/Norwegian/Swedish/Danish/Finnish/Russian/Czech/Hungarian/Polish/Slovene/Turkish/Greek/Simplified Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/Croatian/Vietnamese
Interface Type - PC / Mac	Hi-Speed USB (B Port) Ethernet: 10/100Mbps (auto switchable) Wi-Fi: IEEE802.11 b/g/n Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP, Administration password Wireless LAN Frequency Band: 2.4GHz



TECHNICAL SPECIFICATIONS

PIXMA G7050

Interface Type - Other	Canon PRINT Inkjet/SELPHY app Easy-PhotoPrint Editor Message In Print app PIXMA Cloud Link Canon Print Service Plugin (Android) Google Cloud Print Apple AirPrint Wireless Direct Access Point Mode LAN/WLAN PictBridge Mopria (Android)
SOFTWARE	
Supported Operating Systems	Windows 10, Windows 8.1, Windows 7 SP1 Operation can only be guaranteed on a PC with pre-installed Windows 7 or later. Printer driver and IJ Network Device Setup Utility are available with following OS. Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 OS X 10.10.5~OS X 10.11, macOS 10.12~macOS 10.14
Supported Mobile Systems	iOS, Android, Windows 10 Mobile
Minimum System Requirements	Windows: 2.0GB or more Mac: 1.0GB or more Note: for bundled software installation. The necessary amount of hard disk space required. Display: 1024 x 768 XGA
Software Included	MP Driver IJ Printer Assistant Tool Easy-PhotoPrint Editor (download)
PHYSICAL FEATURES	
Weight	approx. 9.6kg
Dimensions (W x D x H)	approx. 403 x 369 x 234 mm
Acoustic Noise Levels	approx. 47.0dB(A) ^[9]
Operating Temperature	5-35°C
Operating Humidity	10-90%RH (no dew condensation)
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Off: Approx. 0.3W Standby (connected to PC via USB): Approx. 1.0W (scanning lamp off) Standby (all ports connected): Approx. 1.8W (scanning lamp is off) Time to enter Standby mode: 11 min 10sec Copying (USB connection to PC): Approx. 15W ^[10] 0.19kWh ^[11]
Typical Electricity Consumption (TEC)	

Footnotes

- ^[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch
- ^[2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.
- ^[3] Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
- ^[4] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart and continuous printing simulation with the replacement ink bottles after initial setup.
- ^[5] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial setup.
- ^[6] Optical resolution is a measure of maximum hardware sampling resolution based on ISO 14473 standard.
- ^[7] The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.
- ^[8] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.
Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735.
Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- ^[9] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.
- ^[10] Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- ^[11] Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.
- ^[12] Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- ^[13] Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.



Live for the story_

Canon Inc.
canon.com
 Canon Europe
canon-europe.com
 English edition
 Canon Europa NV 2019

MEGATANK 4-IN-1 WITH ADF

PIXMA G7050

Print, scan, copy and fax from one sleek model, boosting uptime with a 350-sheet plain paper capacity, auto 2-sided printing and 35-sheet ADF. Print up to 18,000 pages from 3 ink bottles or 7,700 from a colour set¹ for high quality and low costs.

Sales Start Date: TBC



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
PIXMA G7050	3114C008AA	4549292151473

CONSUMABLES:

Product Name	Mercury Code	EAN Code
GI-50 (PGBK)	3386C001AA	4549292134155
GI-50 (C)	3403C001AA	4549292134179
GI-50 (M)	3404C001AA	4549292134193
GI-50 (Y)	3405C001AA	4549292134216

Canon

Live for the story_

MEGATANK 4-IN-1 WITH ADF

PIXMA G7050

Print, scan, copy and fax from one sleek model, boosting uptime with a 350-sheet plain paper capacity, auto 2-sided printing and 35-sheet ADF. Print up to 18,000 pages from 3 ink bottles or 7,700 from a colour set¹ for high quality and low costs.



MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)	Net Weight (kg)
PIXMA G7050	3114C008AA	Individual	1	500	538	333.8	12.98	10.3
		Pallet (Upper)	12	1003	1089	1059	157.80	123.6
		Pallet (Bottom)	16	1003	1089	1339.7	209.70	165

What's in the box?

- Multifunctional refillable ink tank printer – PIXMA G7050
- 6 high-yield ink bottles (3x Black and 1x C/M/Y)
- Power cord
- Setup CD-ROM
- Manuals and other documents

